

HP Digital

EN

ASTM
D2240

DIN
EN ISO
868

DIN
ISO
48-4

The Bareiss HP Digital is designed to provide ease of use without compromising on precision.



This cost effective durometer is our answer for customers who seek a simple and fast testing operation without compromising the quality of the measuring results. Bareiss has been known for producing the highest quality hardness testing instruments since 1954 and the first generation of the HP model became an iconic representation of how a durometer looks today.

The HP Digital durometer offers every conceivable digital convenience available for a durometer. It can store and display up to 100 sets of measuring data with a Type-C USB interface for exporting data once the limit is exceeded. Additionally, it includes features such as the ability to select the measuring time, switch between peak value and standard value, and provide a visual indication when the measurement is completed.

MEASURING METHODS

Shore A

Shore D

HP Digital

EN

ASTM
D2240

DIN
EN ISO
868

DIN
ISO
48-4

MAIN FEATURES

Up to 100 sets of traceable measurements Incl. date, time, Standard and peak hardness values.

Large visual display.



Type C USB interface for data export.

Intuitive navigation.

TECHNICAL SPECIFICATIONS

Dim. W x H x D 6,5 x 7,8 x 2,6 cm

Weight 182 g (approx.)

Resolution 0.4 Shore

Display type 7 segment LED

Battery Non-chargeable lithium battery CR2477

Working capacity More than 450 hrs (approx.)

Memory capacity 100 measurements

Comm. interface USB Type-C

Spring force

Shore A

8050 mN

Shore D

44500 mN

Displacement

2.5 mm

2.5 mm

Presser foot

Ø 18 mm

Ø 18 mm

Indenter

□ 35°

▽ 30°

HP Digital

EN

ASTM
D2240

DIN
EN ISO
868

DIN
ISO
48-4

ACCESSORIES



Manual test stand, type BS 61

The test stand with manual lowering guarantees the precise 90° support of the handheld hardness tester.



Control rings with DAkkS calibration certificate

The measuring path of the hardness tester, within the defined hardness range, is monitored with the help of the control rings.



Control device for checking the spring force

A / D The control device can be used to check the spring force of the handheld hardness tester.



Reference blocks with DAkkS accredited calibration certificate, single set/set of 3 or 6

Reference blocks can be used to check the indenter, measuring path and spring force of the hardness tester according to DIN ISO 48-4.



**DAkkS accredited
calibration certificate** The calibration takes place according to DIN EN ISO/IEC 17025, being confirmed with a DAkkS accredited calibration certificate.

REFERENCE

The decision to use a test stand will ensure that the HP is placed at an angle of 90° on the test specimen. Alternatively, you can also use our handheld hardness testers HPE III or HPE III Basic, equipped with a functional handle. Thanks to their integrated compression sleeve, these can be guided vertically in a reliable manner, and safely placed on the test specimens, with standard compliant pressure.

MADE IN GERMANY SINCE 1954.

Bareiss Prüfgerätebau GmbH

DAkkS-Kalibrierlaboratorium

Breiteweg 1

89610 Oberdischingen, Germany

Tel +49 (0) 7305 / 96 42-0

Fax +49 (0) 7305 / 96 42-22

sales@bareiss.de



Durch die DAkkS nach DIN EN ISO/IEC 17025:2018 akkreditiertes Laboratorium. Die Akkreditierung gilt nur für den in der Urkundenanlage D-K-15206-01-00 aufgeführten Akkreditierungsumfang.